S1-03P-3225

Compact low power consumption microwave distance sensor

obtained by power measurement on a stimulated receiving

oscillator

Pulsed radar sensors are often used to measure distances with

the aid of microwaves. The methods and arrangements for

constructing and operating pulsed radar sensors exist in a

plurality of forms and have long been known, for example from

documents US 3,117,317, US 4,132,991 and US 4,521,778. Pulsed

radar sensors are used in industrial measurement technology as

height of fill sensors, in motor vehicles as parking aids or

proximity sensors for collision avoidance, and in autonomous

vehicles and transport systems, involving for instance

conveyor mechanisms and automatic plants, for mapping

surroundings and for navigation.

In the applications listed above, pulsed radar sensors usually

operate at center frequencies of approx. 1 GHz to 100 GHz with

typical pulse lengths of 100 ps to 20 ns. Due to the size of

the bandwidth, such sensors have for some time been designated

ultrawideband (UWB) radar. Common to almost all pulsed radar

sensors is the fact that the pulsed signals have so large a

bandwidth that they cannot be directly recorded and processed

by the customary signal acquisition methods, and first have to

be converted to a lower frequency. For this purpose almost all known pulsed systems use a method known as sequential sampling. According to this principle, already known from early digital sampling oscilloscopes, the measurement signal is sampled over a plurality of measurement cycles, the sampling instants being shifted sequentially from one cycle to the next.

According to documents US 3,117,317, US 4,132,991 and US 4,521,778 the switching technology for implementing the sequential sampling involves sending a transmit pulse at a particular repetition rate CLK-Tx (clock transmission), its return being sampled with the aid of a scanning gate at a repetition rate CLK-Rx (clock reception). If the frequencies of the transmit sequence and the sampling sequence differ very slightly, the two sequences gradually shift their phase relative to one another. This gradual shift in the sampling point relative to the transmit moment produces a sequential sampling process.

Fig. 1 shows a known embodiment of a pulsed radar having sequential sampling and operating according to the prior art. The output signal of a continuously operating oscillator is split into a transmission path and a reception path. Both these signals are briefly gated via the switches SW-Tx/SW-Rx having the clock CLK-Tx/CLK-Rx, generating two cyclical pulse

sequences $s_{TX}(t)$ and $s_{TX}(t)$ having slightly different clock

rates. The pulse sequence $s_{TX}(t)$ is transmitted via the antenna

ANT-Tx. The pulse sequence $s_{RX}(t)$ is fed to the first gate of

the mixer MIX, which acts as a scanning gate. The second gate

5   of the mixer is fed with the receive signal reflected from the

objects TARGET1 and TARGET2. The received pulse sequence is

mixed into the low-frequency baseband in the mixer MIX. The

resulting sample pulse sequence is smoothed by a band-pass

filter, producing the low-frequency measurement signal $s_m(t)$.

10

As Fig. 2 shows, an embodiment is also known in which a common

antenna is used for transmitting and receiving, rather than

separate antennas as in Fig. 1, the transmit and receive

signals being mutually separated by for example a circulator

15   or directional couplers.

When taking measurements using sequential sampling and the

conventional radar topology shown in Figs. 1 and 2, the

following disadvantages arise:

20

  - If the measurement signal $s_m(t)$ is acquired as a real number,

    the amplitude of the return pulse changes as a function of

    the specific phase between the transmit signal and the

    receive signal. If the object TARGET2 moves, the pulse

25   envelope belonging to said object "wafts" back and forth,

    as shown in Fig. 3 (labeled TARGET2), as a function of the

momentary reflection phase between the values +A and −A,

determined by the respective distance of the moving object

TARGET2, and the position of the pulse envelope moves

simultaneously with the changing position of the object.

5   Between these extremes the envelope sometimes disappears

completely. If the object to be measured reflects with

precisely a phase at which the pulse envelope disappears,

the object is not detected.

10   - By acquiring the measurement signal $s_m(t)$ as a complex value,

a pulse envelope that does not "waft", as shown in Fig. 6,

can be formed by computing a value from the real part and

the imaginary part of the measurement signal. However, this

requires complex measured values to be acquired, which means

15   using two mixers, and two signals $Re\{s_m(t)\}$ and $Im\{s_m(t)\}$

have to be analyzed.

- The switches SW-Tx/SW-Rx enable only a limited amount of

switch contrast. This means that a signal is always

20   transmitted and a Doppler signal can be seen between the

pulse envelopes. Moreover the transmitted continuous-wave

signal can present a problem with regard to the spurious

emissions permitted by the authorities.

25   - The oscillator HFO is always on and consuming current. In

battery-operated applications this reduces the battery life.

- In the case of RF, an oscillator and two switches which are costly to design are needed to generate the pulses.

An arrangement according to Fig. 4 solves some of the problems mentioned. The function corresponds in the main to the arrangement shown in Fig. 1, the pulse sequences in this case being produced by briefly switching on the signal sources HFO-Tx/HFO-Rx by means of a short voltage pulse from PO-Tx/PO-Rx. Here too the resulting pulse sequences have slightly different clock rates CLK-Tx/CLK-Rx.

In order to obtain a good signal-to-noise ratio (SNR) for the measurement signal, it is essential that the oscillators PO-Tx/PO-Rx are in a deterministic, not stochastic phase relation to one another for all the pulses in a sequence. A deterministic relationship is obtained when the pulse signals which switch on the pulsed oscillators HFO-Tx/HFO-Rx are very rich in harmonic components in the frequency band of the radio-frequency oscillators. The harmonics ensure that the oscillators do not build up their oscillations stochastically, but instead have a locked, characteristic start phase relative to the voltage pulses PO-Tx/PO-Rx. Thus the output signals of both oscillators are also in a deterministic phase relation and time relation to one another, determined by the transmit signal sequence and the sampling signal sequence.

The advantages of the arrangement shown in Fig. 4 are:

- The system has a significantly lower current drain than that
  shown in Fig. 1, since the radio-frequency oscillators are

5   switched off for most of the time during a measurement
     cycle.

- The system has no costly radio-frequency switches.

However there are some disadvantages:

10

- A high cost is involved in the generation of sufficiently
  strong, short voltage pulses that are rich in harmonics.

- If the harmonics are very weak, the build up phase is also

15   affected by other intrusive signals and the measurement
     signal amplitude roars and jitters.

- To determine the distance based on the measurement signal it
  is usually necessary to determine the signal envelope. As a

20   rule this requires the low-frequency measurement signal to
     undergo very high amplification, which is likewise costly to
     provide.

In another area of technology, namely that of transponders, it

25 is known from document US 5,630,216 that both the phase and
    the speed at which an oscillator builds up its oscillations

are affected by an induced signal of a similar frequency. This effect is used for the very low-power demodulation of an incoming AM code signal. However, this amplification effect is not suitable for a single-frequency measurement method such as

5   that previously described.

The object of the present invention is to demonstrate systems which fulfill the object of the described radar arrangements in another, improved form.

10

This object is achieved by means of the inventions specified in the independent claims. Advantageous embodiments will emerge from the dependent claims.

15   In accordance with this solution, an arrangement or device has transmission means for generating and sending an electromagnetic signal, and also has reception means for receiving a return from the transmitted electromagnetic signal. The reception means has a receiving oscillator whose

20   transient response, in particular the build-up time including the average delivered power, can be influenced by the strength, and particularly the amplitude, of the received reflection of the transmitted electromagnetic signal. The receiving oscillator is therefore wired so that it can be

25   excited and/or stimulated by a reflection of the transmitted electromagnetic signal, and because of this a measurement

signal can be generated as a function of the strength, and in
particular the amplitude, of the reflection of the transmitted
electromagnetic signal.

5   For this purpose the arrangement preferably has a detector by
which the average power of the receiving oscillator can be
measured.

It is further advantageous if the arrangement is designed for
10   pulse mode in the transmit and/or receive paths, by fitting
the transmission means and/or the reception means with a means
for switching on and off periodically. In particular the
arrangement can have a means for switching the receiving
oscillator on and off periodically using a clock rate.

15

In a particularly cost-effective and space-saving manner, the
receiving oscillator can be wired in such a way that it also
acts as the transmitting oscillator for generating the
electromagnetic signal for transmission.

20

Alternatively the arrangement can have a second oscillator
acting as the transmitting oscillator for generating the
electromagnetic signal for transmission.

25   In particular the arrangement is an arrangement for measuring
distance, a radar, preferably a pulsed radar.

For detecting a measurement signal, said arrangement can have
a mixer in which a first measurement sub-signal and a second
measurement sub-signal are added together, in particular a
mixer with two diodes, such that the said diodes are used with
the same polarity, that is to say parallel, the measurement
signal being formed by the sum of two measurement sub-signals,
or such that the said diodes are used with opposite polarity,
that is to say antiparallel, the measurement signal being
formed by the difference between the two sub-signals. The
advantage in using such a symmetrical mixer consists in the
doubling of the measurement signal amplitude and in the
particularly good transmission characteristics, which are
especially desirable for sending the transmission signal with
low attenuation as well as for stimulating the receiving
oscillator by means of a receive signal.

In the case of a measurement method, in particular a method
for measuring distance:

- a means of transmission is used to generate and send an
  electromagnetic signal,

- a means of reception having a receiving oscillator is used
  to receive a return, that is a reflection, of the
  transmitted electromagnetic signal,

-9-

- the transient response of the receiving oscillator, in

   particular its build-up time including the average delivered

   power, is influenced by the strength and particularly the

5   amplitude of the reflection of the transmitted

   electromagnetic signal.

Advantageous embodiments of the method are produced in similar

ways to the advantageous embodiments of the arrangement.

10

Further advantages and features of the invention will emerge

from the description of exemplary embodiments, in which;

Fig. 1 shows a pulsed radar according to the prior art;

15

Fig. 2 shows a second pulsed radar according to the prior art;

Fig. 3 shows a measurement carried out using the pulsed radar

according to Fig. 1 or the pulsed radar according to Fig. 2;

20

Fig. 4 shows a third pulsed radar according to the prior art;

Fig. 5 shows an arrangement with means of transmission and

reception;

25

Fig. 6 shows a measurement carried out using the arrangement

according to Fig. 5;

Fig. 7 shows an alternative arrangement with means of
transmission and reception;

5

Fig. 8 shows another alternative arrangement with means of
transmission and reception;

Fig. 9 shows a mixer that can be used in the said

10   arrangements.

Arrangements are described below which avoid the disadvantages
of the systems in Figs. 1, 2 and 4.

15   As already mentioned, both the phase and the speed at which an
oscillator builds up its oscillations are affected by an
induced signal of a similar frequency. When influenced by a
received signal of a similar frequency, an oscillator which is
periodically switched on and off builds up its oscillations

20   more quickly than would be the case without such a signal. The
greater the amplitude of the incoming signal at the switched
oscillator, the shorter the settling time of the oscillator
and the longer it oscillates during a given operating time.

25   If the output signal from a switched oscillator which has been
stimulated by a receive signal is fed through a low pass

filter to a detector DET, the function of said detector in

this arrangement is that of a power meter which measures the

average power output of the stimulated oscillator. If the

oscillator is stimulated by an AM receive signal, the average

5   output power of the oscillator fluctuates as a function of the

signal amplitude of the stimulating signal being received by

the oscillator at any given moment. The measurement signal

$s_m(t)$ is thus a highly amplified representation of the AM

receive signal.

10

In the present case, the switched-oscillator amplification

effect is used to produce a very simple proximity radar with

extremely low power consumption according to the sequential

sampling method. Such a radar system is shown in Fig. 5.

15

This radar system has a transmitting oscillator HFO-Tx which

is periodically switched on briefly by means of a fast-acting

switch PO-Tx with a clock rate CLK-Tx. Typical on periods are

100 ps - 20 ns and typical clock rates are 0.1 - 10 MHz. The

20   signal is transmitted via a diplexer DIP, which in the case

shown takes the form of a circulator. After being reflected

from an object, said signal is received back via the diplexer

DIP and passes through a detector DET to a receiving

oscillator HFO-Rx. Said receiving oscillator HFO-Rx is in the

25   form of a local oscillator and is switched on and off by a

switch PO-Rx with a clock rate CLK-Rx. If components of the

-12-

reflected receive signal are present on the local oscillator
HFO-Rx at the moment it is switched on, due for example to the
practically unavoidable coupling of the receiving antenna via
the detector DET to the local oscillator HFO-Rx, then as
described above, these signals cause the oscillator to start
up more quickly in comparison with the case when the
oscillator starts up due to noise. During distance
measurement, the incoming returns are distributed over time
and vary in strength according to the reflector scenario. Thus
receive signals of varying strength travel via the antenna
ANT, diplexer DIP and detector DET to the local oscillator
HFO-Rx. The strength of the reflection at the moment of
switching on is represented as the average on period of the
oscillator, that is to say, the average oscillator power. The
detector DET uses this average oscillator power to form the
pulse envelope shown in Fig. 6.

The advantages of this system topology and measurement method
are shown in the following points:

- Since the measurement signal $s_m(t)$ is generated by power
  detection rather than by a coherent mixing method, there is
  no "wafting" of the signal amplitude relative to the phase
  of the reflection, even for a moving reflector TARGET2. The
  measurement signal therefore does not need to be generated
  as a complex value.

-13-

- Typical reflections give rise to a range of measurement

   signal amplitudes amounting to some hundreds of millivolts,

   in contrast to mixed signals which, in a coherent system,

5   typically amount to a few tens of millivolts. It is thus

   possible to make savings on amplifier stages of 20-30 dB in

   the LF range without additional expenditure on switching

   technology in the RF range.

10 - The radar system then requires extremely low power

   consumption in order to work.

   - At RF frequencies, only two oscillators are needed to

   generate the pulses. Obtaining the harmonics content in the

15   voltage pulses generated by the switches does not involve

   the demanding requirements found in the case of the voltage

   pulses from the switches SW-Rx or SW-Tx for the arrangement

   seen in Fig. 4.

20 Fig. 7 shows a particularly simple embodiment of the radar

   system. The oscillator HFO acts both as a transmitting

   oscillator and as a stimulated receiving oscillator which is

   switched on not only by the switch PO-Tx with the clock rate

   CLK-Tx, but also by the switch PO-Rx with the clock rate CLK-

25 Rx. Alternatively switching on can also be handled by an

   arrangement such as that shown in Fig. 8. A precondition for

this however is a switch that can produce extremely fast pulse repetition rates.

It is advantageous but not imperative if the detector DET in
5   the system shown in Fig. 7 and Fig. 8 takes the form of a symmetrical mixer based on a 90° hybrid (for an example see A. Maas: "The RF and Microwave Circuit Design Cookbook", Artech House 1998, pp. 107 - 109), as shown in Fig. 9 with a distinguishing feature. The said distinguishing feature
10 consists in the fact that both diodes, as in the case of a frequency doubler, are used with the same polarity, that is to say parallel, the measurement signal being formed however by the sum of two measurement sub-signals $s_{m1}(t)$ and $s_{m2}(t)$, or the said diodes are used with opposite polarity, that is to say
15 antiparallel, the measurement signal being formed by the difference between the two sub-signals. By this means the amplitude of the measurement signal is doubled in comparison with an arrangement using only one diode or picking up only one of the sub-signals $s_{m1}(t)$ or $s_{m2}(t)$. The advantage in using
20 a symmetrical mixer according to Fig. 9 consists further in its particularly good transmission characteristics, which are especially desirable for stimulating the oscillator by means of a receive signal.

25 Unlike the mixer shown here, in a conventional mixer the measurement signal is formed by either using the two diodes in

antiparallel mode and adding the sub-signals together or using

the diodes in parallel and subtracting the two sub-signals. In

contrast to a conventional mixer, the diodes in the mixer

introduced here are not adjusted to give low reflection, but

5 are deliberately intended to be highly resistive and thus

reflective (typically 100 Ω - 100 kΩ in a 50-Ω system). If

necessary a series resistor R can be wired in series with the

diodes in order to obtain the highly resistive characteristic.

10 Besides the advantages already mentioned for the system shown

in Fig. 5, it is also true to say that this system is very

simple. Only one RF oscillator is needed for generating the

pulses.

15 Embodiments:

- Using the radar sensor described, all the other methods

commonly used in pulsed radar systems for measuring distance

can also be used in place of the sequential sampling method.

20 A radar system can then be made sensitive to only one given

proximity range by making the two clock rates CLK-Tx and

CLK-Rx identical but offset relative to each other by one

time period corresponding to the signal propagation time

between the sensor and the proximity range being monitored.

25 In this operating mode the system could be used as an

excellent and very cost-effective limit switch (for instance

in industrial measurement technology for height of fill to

prevent overflow or under-filling) or as a type of radar

barrier (for example to count and/or detect persons and

vehicles, or to detect objects on flow lines).

5

- Similarly [neither] the clocks CLK-Tx and CLK-Rx nor the

offset of the clocks relative to one another need be regular

in order to produce a complete distance profile, but it is

also possible to create a series of sampled values according

10   to any scheme (e.g. stochastic or coded) via the object

scene and then assign and allocate the distance measurement

points correctly in relation to one another in an analytical

unit. Further methods for operating the radar are

imaginable.

15

- In place of the circulator seen in Fig. 5, the separation

between transmission and reception can also be achieved with

the aid of a directional coupler, or may be dispensed with

entirely. In the latter case the antenna can be connected

20   via a single spur line. However, significantly worse

distance measurement performance is to be expected in this

instance, since direct crosstalk from the transmission path

to the reception path, or reflected signals on the spur

line, have the same effect as a very close reflector.

25

- As is usual with pulsed radar systems, the unambiguous range

of the radar is defined by the pulse repetition rate. Reflected pulses which arrive at the radar sensor only after the next outgoing pulse has been transmitted are interpreted as very close reflectors. Since the average received energy defines the S/N ratio, it is desirable to choose a high pulse repetition rate and thus inevitably the narrowest possible unambiguous range.

- The order of magnitude of the on period of CLK-Tx and CLK-Rx must be within the range Q oscillation cycles of the oscillators HFO-Tx/HFO-Rx, where Q represents the weighted quality of the resonator in the oscillator. Otherwise the oscillator cannot completely build up to its maximum amplitude during the settling time. In this respect the resonator should have as low a quality as possible.

- Unlike many pulsed radar sensors (such as that in Fig. 4) it is not necessary for the starting pulse to build up particularly steeply and generate harmonics in the radio frequency range.

Because of their particularly simple and cost-effective structure, the radar arrangements are ideally suited for all cost-sensitive applications. Those which should be singled out for mention are proximity sensors around motor vehicles (parking aids, blind-spots, airbags, pre-crash detection,

automatic navigation and sensors in general for autonomous

vehicles), proximity sensors inside motor vehicles (seat

occupancy monitoring, intrusion alarms, crush protection

systems for windows and sliding roofs), the entire range of

5   industrial distance sensors and the range of sensors for

household use (monitoring of windows, doors, rooms and

boundaries).